Applicant: RUTH, Karsten, et al.

Serial No.: 10/541,173

Filing Date: February 6, 2006

February 4, 2010 Response to August 6, 2009 Office Action

Page 3 of 8

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in this application.

1. (currently amended) Catalyst-containing gas diffusion layer for a fuel cell, which comprises comprising a porous support material and catalyst particles, wherein the catalyst particles which are distributed uniformly over the entire volume of the gas diffusion layer.

2. (canceled)

3. (previously presented) Catalyst-containing gas diffusion layer according to Claim 1, wherein the catalyst particles have a mean particle size of from 1 to 100 nm.

4. (previously presented) Catalyst-containing gas diffusion layer according to Claim 1, wherein the catalyst particles comprise a noble metal selected from the group consisting of Pt, Pd, Ru, Rh, Au, Ag, Ir, and Os, or an oxide thereof, or a mixture thereof, or an alloy thereof with a base metal.

5. (previously presented) Catalyst-containing gas diffusion layer according to Claim 1, wherein the catalyst particles are present on the gas diffusion layer in a concentration per unit area of from 0.01 to 100 mg of metal/cm².

6. (previously presented) Catalyst-containing gas diffusion layer according to Claim 1, wherein the porous support material comprises woven carbon fibre fabric, carbon fibre nonwoven, carbon paper, carbon fibre mesh, synthetic fibre mesh coated with conductive material, woven polymer fibre fabric coated with conductive material, glass fibres coated with conductive material, foam coated with conductive material or woven metal fibre fabric or metal wire mesh.

Applicant: RUTH, Karsten, et al.

Serial No.: 10/541,173

Filing Date: February 6, 2006

February 4, 2010 Response to August 6, 2009 Office Action

Page 4 of 8

7. (previously presented) Catalyst-coated gas diffusion layer according to Claim 1,

wherein the catalyst particles are gas-phase-active and are suitable for the oxidation of

carbon monoxide.

8. (previously presented) Catalyst-containing gas diffusion layer according to Claim 1,

wherein the catalyst particles are gas-phase-active and are suitable for the conversion of

carbon monoxide into methane.

9. (previously presented) Catalyst-containing gas diffusion layer according to Claim 1,

wherein the catalyst particles are suitable for the oxidation of methanol.

10. (withdrawn) Process for producing a catalyst-containing gas diffusion layer according

to Claim 1, wherein the catalyst particles are formed on the porous support material by

thermal decomposition of at least one precursor compound.

11. (withdrawn) Process for producing a catalyst-containing gas diffusion layer according

to Claim 10, wherein the porous support material is treated with at least one

precursor compound, is dried and is heat treated, with decomposition of the

precursor compound occurring and the catalyst particles being formed and

immobilized on the surface of the support material.

12. (withdrawn) Process for producing a catalyst-containing gas diffusion layer according

to Claim 10, wherein a thermally decomposable metal compound is used as a precursor

compound.

13. (withdrawn) Process for producing a catalyst-containing gas diffusion layer according

to Claim 10, wherein one or more metal compounds selected from the group consisting of

nitrates, carbonates, carboxylates, hydroxycarboxylates, acetates, lactates, butanoates,

oxalates, formates, resinates and ethylhexanoates are used as precursor compound.

Applicant: RUTH, Karsten, et al.

Serial No.: 10/541,173

Filing Date: February 6, 2006

February 4, 2010 Response to August 6, 2009 Office Action

Page 5 of 8

14. (withdrawn) Process for producing a catalyst-containing gas diffusion layer according to Claim 10, wherein the thermal decomposition comprises heat treatment which is

carried out at a temperature of from 200 to 900°C.

15. (withdrawn) Process for producing a catalyst-containing gas diffusion layer according

to Claim 10, wherein the thermal decomposition comprises heat treatment which is

carried out under a gaseous atmosphere, preferably under air, nitrogen, hydrogen or

mixtures thereof.

16. (withdrawn) Process for producing a catalyst-containing gas diffusion layer according

to Claim 10, wherein the production is carried out in a continuous process.

17. (previously presented) A fuel cell for the removal of carbon monoxide from

hydrogen-containing fuel gases comprising the catalyst-containing gas diffusion layer of

Claim 1.

18. (previously presented) A direct methanol fuel cell for oxidation of methanol

comprising the catalyst-containing gas diffusion layer of Claim 1.

19. (previously presented) Membrane-electrode unit for a low-temperature fuel cell,

which comprises a catalyst-containing gas diffusion layer according to Claim 1.